


WONDERFLOOR

www.wonderfloor.co.in

TIMBERLAND HERRINGBONE
2.00 mm



**MADE
in
INDIA**

Premium Herringbone Strips



Fire Resistant



Termite Proof



Environment Friendly



Moisture Proof



PUR guard for low maintenance & surface protection against dirt

WONDERFLOOR

www.wonderfloor.co.in

TIMBERLAND HERRINGBONE

2.00 mm



HBN 01




HBN 02



HBN 03



HBN 04




TIMBERLAND HERRINGBONE
2.00 mm



HBN 05



HBN 06



HBN 07




HBN 08




TIMBERLAND HERRINGBONE

2.00 mm



HBN 09




HBN 10

HERRINGBONE PATTERNS



PATTERN 01



PATTERN 02



PATTERN 03



PATTERN 04

Timberland Herringbone Dimensions:

18 inch

4 inch


WONDERFLOOR - The world-class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2015 systems certified company. We are the largest manufacturer & exporter of PVC floor coverings, film, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in state-of-the art plant & machinery equipped with latest technology and optimum quality control. Wonderfloor has a wide sales distribution network across India.

TIMBERLAND HERRINGBONE is the latest collection of Premium Herringbone strips. The shades and designs are carefully chosen to complement the natural wood & stone. Manufactured with multi-layer hot press technology, this premium flooring is highly suitable to handle moderate footfalls. The PUR protection layer ensures trouble free performance and enhance durability. It reduces the noise impact, is trendy, quick to install, easy to use and maintenance free. Finally, Timberland Herringbone is termite resistant, moisture resistant & fire resistant. Timberland Herringbone strips are recommended for hotels, stores, malls, cafeteria, schools, banks, homes, offices etc.

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	RESULTS
TYPE OF FLOORING	EN 649	RESILIENT FLOORING
OVERALL THICKNESS	EN 428 / IS: 3464	2.00 mm*
DIMENSION (SIZE)	EN 427 / IS: 3464	101.6mm x 457.2mm (4"x 18")
SQUARENESS	IS: 3464	≤ 0.15 mm
WEAR LAYER		0.20mm (HEAVY DUTY)
DENSITY	EN 430	3700 g/m ²
DIMENSIONAL STABILITY	EN 434	≤ 0.25%
RESIDUAL INDENTATION	EN 433	≤ 0.10 mm
COLOR FASTNESS	ISO 105 B02	CLASS 6
FIRE RATING	EN 13501 - 1	Bfl-S1
HORIZONTAL & VERTICAL BURNING TEST	IS 15061 - 2002	PASS (ARAI)
PERFORMANCE CLASSIFICATION	EN 685	34/41
ABRASION RESISTANCE	EN: 660-2	Wear Group P
SOUND ABSORPTION	ISO 140-8/EN ISO 717-2	ΔLW=5db
SLIP RESISTANCE	DIN 51130	R9
BEARING CASTOR CHAIR	EN 425	SUITABLE / CONTINUOUS USE
SURFACE PROTECTION	PUR	PUR
MOISTURE MOVEMENT	APPENDIX B OF IS: 3462	≤ 0.40%
RESISTANCE TO STAINING	EN 423	PASS
PATTERN		WOOD and STONE
No. OF PCS PER BOX & AREA OF BOX		72 PCS / BOX = 3.34 SQM / BOX (36 SQ.FT)

* Thickness: 3.0 mm can be produced against bulk quantity orders



RECOMMENDATION FOR INSTALLATION

Wonderfloor Vinyl Plank must be allowed to relax for 24 hours in room temperature between 18°C and 27°C prior to installation. Vinyl planks are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, dry and free from grease & grit. Wonderfloor recommends use of Fevicol SR 998, Fevicol SR 505 or any other equivalent rubber/acrylic/water based adhesive of similar type.

MAINTENANCE

Do's: • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail : mkt@rmgpoly.com or call : +91 9015313059 (Available between 10am-6.30pm)

For export enquiries, please e-mail : info@rmgpoly.com or call : +91 9873138885

RMG POLYVINYL INDIA LIMITED

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited

