

**WONDERFLOOR**

[www.wonderfloor.co.in](http://www.wonderfloor.co.in)

**METEOR**

**PUR**

**Protection**

PUR guard for  
low maintenance &  
surface protection  
against dirt

**MADE  
in  
INDIA**

**Premium Flooring**

**METEOR**



311011



311012



311013



557811



557812



557813



558201



558202



558203



558204



559601



559602

**WONDERFLOOR**

[www.wonderfloor.co.in](http://www.wonderfloor.co.in)

**METEOR**



559603



NIMS Medical College – Jaipur



IIT – Hyderabad



Brains super specialty hospital - Bangalore



NIMS Medical College – Jaipur



**WONDERFLOOR** - The world-class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2015 systems certified company. We are the largest manufacturer & exporter of PVC floor coverings, film, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in state-of-the art plant & machinery equipped with latest technology and optimum quality control. Wonderfloor has a wide sales distribution network across India.

**METEOR** is a premium flooring range available in rolls of 2.0 mm thickness with a wide range of classic wood design and real wood like top surface. Its also available in non directional chip design. Meteor has been designed to withstand moderate footfalls and is ideal for semi commercial applications like offices, shops, small stores, boutique, libraries, large halls and area of similar usage.

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	RESULT
THICKNESS (mm)	EN 428	2.0
ROLL WIDTH (mtr)	EN426	2.00
ROLL LENGTH (mtr)	EN426	15
WEAR LAYER (mm)	EN 429	≥ 0.25
TOTAL WEIGHT (kgs/sq mtr)	EN 430	3.60 ± 5%
SLIP RESISTANCE	DIN 51130	R9
RESIDUAL INDENTATION (mm)	EN 433	≤ 0.10 mm
DIMENSIONAL STABILITY (%)	IS 3464	≤ 0.40%
MOISTURE MOVEMENT (%)	IS 3462	≤ 0.40%
FLEXIBILITY (mm)	EN 435	40 mm MANDREL. PASS
PERFORMANCE CLASSIFICATION	EN 685	33
ABRASION RESISTANCE	EN: 649 / EN: 660-2	WEAR GROUP P
RESISTANCE TO CHEMICAL	ASTM F925	NO VISIBLE CHANGE
COLOUR FASTNESS TO DAYLIGHT	ISO 105-B02	> BLUE WOOL STANDARD 4
FLAMMABILITY	IS 15061	PASSES
SURFACE PROTECTION	PUR	PUR



RECOMMENDATION FOR INSTALLATION

Wonderfloor sheet must be allowed to relax for 24 hours in room temperature between 18°C and 27°C prior to installation. Vinyl rolls are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, dry and free from grease & grit. Wonderfloor recommends use of Fevicol SR 998, Fevicol SR 505 or any other equivalent rubber/acrylic/water based adhesive of similar type.

MAINTENANCE

Do's: • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail : [mkt@rmgpoly.com](mailto:mkt@rmgpoly.com)  
or call : +91 9015313059 (Available between 10am-6:30pm)  
For export enquiries, please e-mail : [info@rmgpoly.com](mailto:info@rmgpoly.com) or call : +91 9873138885

**RMG POLYVINYL INDIA LIMITED**  
WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited

