

WONDERFLOOR

www.wonderfloor.co.in

METEOR



PUR

**MADE
in
INDIA**

Premium Flooring

WONDERFLOOR

www.wonderfloor.co.in


METEOR




311011



311012



311013



557811



557812




557813



558201



558202



558203



558204

WONDERFLOOR - The world-class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2015 systems certified company. We are the largest manufacturer & exporter of PVC floor coverings, film, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in state-of-the art plant & machinery equipped with latest technology and optimum quality control. Wonderfloor has a wide sales distribution network across India.

PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	METEOR
THICKNESS (mm)	EN 428	2.0
ROLL WIDTH (mtr)	EN426	2.00
ROLL LENGTH (mtr)	EN426	15
WEAR LAYER (mm)	EN 429	≥ 0.25
TOTAL WEIGHT (kgs/sq mtr)	EN 430	3.60 ± 5%
SLIP RESISTANCE	DIN 51130	R9
RESIDUAL INDENTATION (mm)	EN 433	≤ 0.10 mm
DIMENSIONAL STABILITY (%)	IS 3464	≤ 0.40%
MOISTURE MOVEMENT (%)	IS 3462	≤ 0.40%
FLEXIBILITY (mm)	EN 435	40 mm MANDREL. PASS
PERFORMANCE CLASSIFICATION	EN 685	33
ABRASION RESISTANCE	EN: 649 / EN: 660-2	WEAR GROUP P
RESISTANCE TO CHEMICAL	ASTM F925	NO VISIBLE CHANGE
COLOUR FASTNESS TO DAYLIGHT	ISO 105-B02	> BLUE WOOL STANDARD 4
FLAMMABILITY	IS 15061	PASSES



RECOMMENDATION FOR INSTALLATION

Wonderfloor sheet must be allowed to relax for 24 hours in room temperature between 18°C and 27°C prior to installation. Vinyl rolls are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, dry and free from grease & grit. Wonderfloor recommends use of Fevicol SR 998, Fevicol SR 505 or any other equivalent rubber/acrylic/water based adhesive of similar type.

MAINTENANCE

Do's: • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail : mkt@rmgpoly.com

or call : +91 9711200510

For export enquiries, please e-mail : info@rmgpoly.com

or call : +91 9873138885 / +91 9953208740

RMG POLYVINYL INDIA LIMITED

WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited

