

**WONDERFLOOR**

[www.wonderfloor.co.in](http://www.wonderfloor.co.in)

# TIMBERLAND EXOTICA

2.00 mm

**MADE  
in  
INDIA**

**REAL  
LVT**  
HOT PRESS  
TECHNOLOGY



**High Performance  
Luxury Vinyl Planks**



Fire  
Resistant



Termite  
Proof



Environment  
Friendly



Moisture  
Proof



PUR guard for  
low maintenance  
& surface  
protection  
against dirt

Image is for illustration purposes only, actual shade may vary in shade and appearance

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Beach Natural 2024



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Burnt Wood 2406

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Oak Premium 2906



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Oak White 2911

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Natural Teak 3040



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Walnut 3062

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Exotic Teak 3111



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Honey Oak 3113

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Antique 3304



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

English Wood 3338

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Classic Dark 3382



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Classy Cane 3383

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Farm Oak 3408



# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Weathery Oak 3571

# TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Exotic Wood 3572



TIMBERLAND EXOTICA

2.00 mm



914.4mm (36 inch)

Dimensions



152.4mm (6 inch)

Cherry 3624

**TIMBERLAND EXOTICA** is the latest collection of PVC wooden plank. The shades and designs are carefully chosen to complement the natural wood. Manufactured with multi-layer hot press technology, this premium flooring is highly suitable to handle moderate footfalls. The PUR protection layer ensures trouble free performance and enhance durability. It reduces the noise impact, is trendy, quick to install, easy to use and maintenance free. Finally, Timberland Exotica is termite resistant, moisture resistant & fire resistant. Timberland Planks are recommended for hotels, stores, malls, cafeteria, schools, banks, homes, offices etc.

## PERFORMANCE CHARACTERISTICS

CHARACTERISTICS	TEST METHOD	RESULTS
TYPE OF FLOORING	EN 649	RESILIENT FLOORING
OVERALL THICKNESS	EN 428 / IS: 3464	2.0 mm
DIMENSION (SIZE)	EN 427 / IS: 3464	152.4mm x 914.4mm ( 6"x 36") 228.60mm x 914.4mm (9"x 36")*
SQUARENESS	IS 3464	≤ 0.15 mm
WEAR LAYER		0.20 mm (Heavy duty)
DENSITY	EN 430	3700 g/m²
DIMENSIONAL STABILITY	EN 434	≤ 0.25 %
RESIDUAL INDENTATION	EN 433	≤ 0.10 mm
COLOR FASTNESS	ISO 105-B02	CLASS 6
FIRE RATING	EN 13501-1	BflS1
HORIZONTAL & VERTICAL BURNING TEST	IS: 15061-2002	PASS (ARAI)
PERFORMANCE CLASSIFICATION	EN 685	34/41
ABRASION RESISTANCE	EN 660-2	WEAR GROUP P
SOUND ABSORPTION	ISO 140-8/EN ISO 717-2	ΔLW=5db
SLIP RESISTANCE	DIN 51130	R9
BEARING A CASTOR CHAIR	EN 425	SUITABLE /CONTINUOUS USE
SURFACE PROTECTION	PUR	PUR
PATTERN		Wood and Classic
NO. OF PCS PER BOX & AREA OF BOX		24 PCS/BOX (1 BOX = 3.34 SQ. MTR/36 SQ. FT)

\*Against bulk orders



### RECOMMENDATION FOR INSTALLATION

Wonderfloor Vinyl Plank must be allowed to relax for 24 hours in room temperature between 18°C and 27°C prior to installation. Vinyl planks are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, dry and free from grease & grit. Wonderfloor recommends use of Fevicol SR 998, Fevicol SR 505 or any other equivalent rubber/acrylic/water based adhesive of similar type.

### MAINTENANCE

Do's: • After laying of flooring, the surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coir brush or fine steel wool soaked in a warm soap solution • Scuff marks on the floor can be removed with little application of diesel • Use door coir or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.  
Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail : [mkt@rmgpoly.com](mailto:mkt@rmgpoly.com) or call : +91 9015313059 (Available between 10am-6.30pm)  
For export enquiries, please e-mail : [info@rmgpoly.com](mailto:info@rmgpoly.com) or call : +91 9873138885

**RMG POLYVINYL INDIA LIMITED**  
WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited

